



Product Datasheet

Special Offers>Industrial & Floodlights

70106D/C



140W LED street light. High lumen output ideal for replacement of old HPS and mercury street lighting fittings.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads





Dimensions



Physical Specification

Item Group	Special Offers
Family	Industrial & Floodlights
Order Code	70106D/C
Colour	Grey
Material	Die Cast
Shape	Rectangular
Length	864mm
Width	375mm
Height	174mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	140W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Type Voltage	80V
Input Type	
Input Type Voltage	80V
Input Type Voltage Power(Watts)	140W
Input Type Voltage Power(Watts) IP Rating	140W IP65
Input Type Voltage Power(Watts) IP Rating Light Source	80V 140W IP65 LED built in
Input Type Voltage Power(Watts) IP Rating Light Source LED Type	80V 140W IP65 LED built in COB
Input Type Voltage Power(Watts) IP Rating Light Source LED Type LED Brand	80V 140W IP65 LED built in COB Cree

Gear Type Led Driver Input Voltage 100-240V Yes 50 Hz 60 Hz Yes Power(Watts) 40W Power Factor 0,9

Constant Current	Yes
IP Rating	IP65
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Illumination Data	
	40004
Colour Temperature	4000K
Lumen Output	10500lm
Light Efficiency	75lm/W
CRI	70
Beam Angle	140° x 70°
Illumination Diagram	
Packing Info	
D. Weith	40.514
Box Weight	13,5Kg
Pcs/Carton	1
Barcode	5291889037903
HS Code	9405409900
Certification & Warranty	
Warranty	2 Years
······································	

switch to one light!

