

21 Industrial & Floodlights>The Classic LED Floodlights Die cast

7032/AN/C



150W Classic LED floodlight, IP65.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Classic LED Floodlights Die cast
Order Code	7032/AN/C
Colour	Anthracite
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular
Length	450mm
Width	260mm
Height	185mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground

Yes

Outdoor

Yes

Adjustable

1 Direction

## Electrical Characteristics

Gear

Built In

### Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

150W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



### Fitting

Input Type

Constant Current

Input Current

4500mA

Voltage

33V

Power(Watts)

148,5W

IP Rating

IP65

Light Source

LED built in

LED Type

COB

LED Brand

Epistar


### Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	121,5-162W
Power Factor	0,95
Constant Current	Yes
Output	4500mA
Voltage Range	27-36V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Meanwell

#### Illumination Data

Colour Temperature	4000K
Lumen Output	12000lm
Light Efficiency	80lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

#### Packing Info

Box Weight	8,6Kg
Pcs/Carton	1
Barcode	5291889032731
HS Code	9405409900

#### Energy Label



## Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

**one**  
LIGHT

