

21 Industrial & Floodlights>The Floodlights

7040/G/D



30W COB LED Slim floodlight, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Floodlights
Order Code	7040/G/D
Colour	Grey
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular
Length	240mm
Width	280mm
Height	145mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground

Yes

Outdoor

Yes

Adjustable

1 Direction

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

30W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

Cable Length

100cm

F Mark



Fitting

Input Type

Constant Current

Power(Watts)

30W

IP Rating

IP65

Light Source

LED built in

LED Type

COB

LED Brand

Epistar

Gear

Gear Type


Led Driver

Input Voltage


100-240V

50 Hz

Yes

60 Hz	Yes
Power(Watts)	30W
Power Factor	0,9
Constant Current	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector

Illumination Data

Colour Temperature	6000K
Lumen Output	2100lm
Light Efficiency	70lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	25cm
Box Width	10cm
Box Height	32cm
Box Weight	2.680kg
Pcs/Carton	5
Barcode	5291889032779
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

