



Product Datasheet

21 Industrial & Floodlights>The LED High Power Box Aluminium

7058R/W/C



IP65, LED High Power Boxes.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Gallery



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The LED High Power Box Aluminium
Order Code	7058R/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	414mm

Width	414mm
Height	100mm
Cutout Hole Width	380mm
Cutout Hole Length	380mm
Recessed Ceiling	Yes
Depth Required	130mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	120W
IP Rating	IP65
Light Source	LED built in
Dimmable	No Variable Control of the Control o
F Mark	F
Fitting	
Fitting	
Input Type	Constant Current
Input Current	4200mA
Voltage	28V
Power(Watts)	118W
IP Rating	IP65
Light Source	LED built in

LED Type	SMD 3030
LED Brand	Osram
LED Number	140
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	118-151W
Power Factor	0,9
Constant Current	Yes
Output	4200mA
Voltage Range	28-36V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Meanwell

Illumination Data

Colour Temperature	4000K
Lumen Output	10800lm
Light Efficiency	90lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Weight	9,4Kg
Pcs/Carton	1
Barcode	5291889042686

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



