

08 Strips & Profiles > Flex Lightline

7810/D



Mains voltage LED strip 4,8W/m.

Supplied in 50m rolls.

Can be cut every 1m.

Requires power supply order code 7814.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions




Gallery




Accessories



7812



7815B/G



7815B/G



7815B/W




7815B/W




Related items



7814



7815/G



7815/G



7815/W




7815/W

Physical Specification


Item Group	08 Strips & Profiles
Family	Flex Lightline
Order Code	7810/D
Material	Silicone
Shape	Rectangular
Length	50000mm
Width	16mm
Height	27mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics


Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	4,8W/m
IP Rating	IP54

Light Source	LED built in
Dimmable	No
F Mark	


Fitting

Safety Class	
Power(Watts)	4,8W/m
IP Rating	IP54
Light Source	LED built in
LED Brand	Sanan

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	240W
Power Factor	0,9
IP Rating	IP54
Safety Class	
Brand	0
Protection	0

Illumination Data

Colour Temperature	6000K
Lumen Output	180lm/m
Light Efficiency	37,5lm/W
Illumination Diagram	

Packing Info

Box Weight	0,57kg
Pcs/Carton	50
Barcode	5291889013945
HS Code	9405403990

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

