\mathbf{P}

Product Datasheet

www.1-light.eu

7813L/W

08 Strips & Profiles>Connect In One Length Range 24V

CE



Flexible LED light strip, with SMD2835 LEDs, 60LEDs/meter, 3W/meter.Supplied in 30 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions

Cut every 10cm (6-LED segment) _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ 10mm

Gallery

£);

Downloads

IES



Physical Specification

Item Group	08 Strips & Profiles
Family	Connect In One Length Range 24V
Order Code	7813L/W
Shape	Rectangular
Length	30m
Width	10mm
Inground	Yes



Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	3W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Refond
LED Number	60Leds/m

Illumination Data

Colour Temperature	3000K
Lumen Output	240lm/m
Light Efficiency	80lm/W
CRI	80
Illumination Diagram	

Box Length	43cm
Box Width	43cm
Box Height	2cm
Pcs/Carton	20
Barcode	5291889058878



Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to one light!



