08 Strips & Profiles>The 9,6W/m 24V SMD2216 140LEDs/m

7829A/W

Flexible LED strip with SMD2835 LEDs, 70LEDs/m, 9,6W/m.

Supplied in 5 meters roll with 3M double face adhesive tape.

Can be cut every 10cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI DIMMABLE CE

Downloads

IES

Dimensions

Cut every 10cm
(7-LED segment)

8mm

Related items

20030

Physical Specification

Item Group	08 Strips & Profiles
Family	The 9,6W/m 24V SMD2216 140LEDs/m
Order Code	7829A/W
Shape	Rectangular
Length	5000mm
Width	8mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	III
Power(Watts)	9,6W/m
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
LED Number	70LEDs/m
F Mark	F

Illumination Data

Colour Temperature	3000K
Lumen Output	864lm/m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

Packing Info

Pcs/Carton	40
Barcode	5291889078500
HS Code	9405499090

ONE Light Ltd
7829A/W

10 kWh/1000h

2019/2015

Energy Class	F

Warranty	5 years

switch to
one light!

one LIGHT