

08 Strips & Profiles > The 9,6W/m 24V SMD2216 140LEDs/m

7829/W



Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items



20030

Physical Specification



Item Group

08 Strips & Profiles


Family	The 9,6W/m 24V SMD2216 140LEDs/m
Order Code	7829/W
Shape	Rectangular
Length	5000mm
Width	8mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	9,6W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	140LEDs/m
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	864lm/m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,18kg
Pcs/Carton	40
Barcode	5291889054528
HS Code	9405409989

Energy Label



Energy Class	F
--------------	---

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

