

08 Strips & Profiles > The RGB & RGBW Strips 24V

7830/RGBW



RGBW flexible LED light strip, with SMD5050 LEDs, 60LEDs/meter, 19,2W/meter. Supplied in 5 meters roll, with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Related items



20036



89100LP

Physical Specification

Item Group	08 Strips & Profiles
Family	The RGB & RGBW Strips 24V
Order Code	7830/RGBW
Shape	Rectangular
Length	5m
Width	12mm
Surface Ceiling	Yes

Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	19,2W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5050
LED Brand	Refond
LED Number	60Leds/m

Illumination Data

Colour Temperature	RGB+3000K
Illumination Diagram	

Packing Info

Box Weight	0,2kg
Pcs/Carton	40
Barcode	5291889048824
HS Code	9405409989

Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

