

One

www.1-light.eu

08 Strips & Profiles>The Flex Tiles

7848/C



standards.

Flexible tile, 10W ideal for cover walls and columns.

Supplied in 480mmx240mm pcs in white PCB and double adhesive tape for a better fixing.

Complete with 2pcs power supply cable and 2pcs tile connectors.

Connect max up to 10pcs with one driver.

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific



Downloads










Dimensions



Gallery





Related items



20030

Item Group	00 String & Profiles
	08 Strips & Profiles
Family	The Flex Tiles
Order Code	7848/C
Shape	Rectangular
Length	480mm
Width	240mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Input Type	Constant Voltage
Fitting	
Input Voltage	24V DC
0-1-1-01	
	(III)
Power(Watts)	10W
Power(Watts) IP Rating	10W IP20
Power(Watts) IP Rating Light Source	10W
Power(Watts) IP Rating Light Source	10W IP20
Power(Watts) IP Rating Light Source LED Type	10W IP20 LED built in SMD 2835 288LEDs/pc
Power(Watts) IP Rating Light Source LED Type LED Number	10W IP20 LED built in SMD 2835
Power(Watts) IP Rating Light Source LED Type LED Number F Mark	10W IP20 LED built in SMD 2835 288LEDs/pc
Power(Watts) IP Rating Light Source LED Type LED Number F Mark ination Data	10W IP20 LED built in SMD 2835 288LEDs/pc
Power(Watts) IP Rating Light Source LED Type LED Number F Mark ination Data	10W IP20 LED built in SMD 2835 288LEDs/pc
Power(Watts) IP Rating Light Source LED Type LED Number F Mark ination Data plour Temperature	10W IP20 LED built in SMD 2835 288LEDs/pc
Safety Class Power(Watts) IP Rating Light Source LED Type LED Number F Mark Innation Data Clour Temperature Jumen Output ght Efficiency	IP20 LED built in SMD 2835 288LEDs/pc



2

Packing Info


Box Weight 0.345kg

Pcs/Carton

Barcode 5291889071341

HS Code 9405499090

Energy Label



Certification & Warranty

Warranty 5 years

switch to one light!

