O_{LIGHT}

Product Datasheet

www.1-light.eu

7860/C

08 Strips & Profiles>The 230V IP65 Range



230V Waterproof LED strip 9W/m, IP65 .

Supplied in 50m rolls.

Can be cut every 1m.

Requires power supply order code 7860P.

Complies with standard EN60598-1 and any other specific standards.



Gallery



Must be ordered separately





7860P





7860C

7860E



7860F



7860L



7860R



Physical Specification

e 230V IP65 Range
60/C
ctangular
000mm
nm
5
5
5
5
S

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9W/m
IP Rating	IP65
Light Source	LED built in
Dimmable	Vos

Dimmable	Yes
Dimmer type	Triac
F Mark	F
Fitting	
Safety Class	
Power(Watts)	9W/m




IP Rating	IP65
Light Source	LED built in
LED Type	SMD 3528
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	450W
Power Factor	0,9
IP Rating	IP65
Safety Class	
Brand	0
Protection	0
Illumination Data	

Colour Temperature	4000K
Lumen Output	750lm
Light Efficiency	100lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.102Kg
Pcs/Carton	50
Barcode	5291889044574
HS Code	9405423100





Certification & Warranty 2 years Warranty 2 years Weee Directive Yes

switch to one light!



