

Product Datasheet

www.1-light.eu

08 Strips & Profiles>230V COB Flex Lightline

7872/C



COB LED strip, 480LEDs/m, 12W/m, 230V, TRIAC Dimmable.

Supplied in 50 meters roll with 3M double face adhesive tape.

Supplied with EU plug and 1m cable.

Can be cut every 10 cm.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions

5mm

Cut every 10cm
(48-LED segment)

12mr

Accessories







7872E



Physical Specification

Item Group	08 Strips & Profiles
Family	230V COB Flex Lightline
Order Code	7872/C
Material	Silicone
Shape	Rectangular

Length	50000mm
Width	12mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Electrical Characteristics	
Gear	No
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W/m
IP Rating	IP66
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	F
umination Data	
Colour Temperature	4000K
Lumen Output	840lm/m
Light Efficiency	70lm/W
CRI	90
Beam Angle	140°
Illumination Diagram	

Packing Info

Box Weight0.106kgPcs/Carton50Barcode5291889078524

9405423100

Energy Label

HS Code



Energy Class G

Certification & Warranty

Warranty 3 years

Weee Directive

Yes

switch to one light!

